Major Applications

Next generation Nano - Ceramic Coatings for,









PPF Nano Coating

Product Overview

PPF Nano Coating is next-generation cera mic coatings suitable for paint protection film. The coatings can be easily applied by spraying the coating directly onto the surface. Our patented technology allows the coatings to deeply penetrate the surface and for massecure and tight bond, thus creating a thick cera mic protective layer. The flashing time for the product varies according to the temperature of the surface and the surrounding and humidity levels. We highly recommend finding the correct application time before usage.

This product has outstanding che mical resistance, gloss, hardness, sleekness, and water repellency.

loch	nical	llata
I GUII	IIIGAI	Duta

→ APPEARANCE	Clear
→ FINISH	Outstanding Gloss
CHEMICAL RESISTANCE	Grade 3 (Min 0 Max 5)
→ COVERAGE	108 sqft / 1.8 ounce (50 ml)
→ SHELF LIFE	12 months from manufacturing date when unopened and stored dry at 18° C (64° F) to 23° C (73° F)
→ DURABILITY	Up to 1 Years with condition of proper maintenance
PENCIL HARDNESS	9 H
FILM THICKNESS	200~400nm
SALT SPRAY (ASTM B117)	@ 35° C (95° F), 5% salt concentration, > 400 hrs to first sign corrosion
→ ADHESION CROSS - CUT TAPE (ASTM D33)	5b (0%, none)
MANDREL BEND (ASTMD522)	0% @ 180° rotation
MPACT (ASTM D2794)	80/80 in/lbs
→ WATER REPELLENCY	120° at 20 μL, glass
OIL REPELLENCY	60° at 20 μL, glass
→ ROLL-OFF ANGLE	11~15° at 20 μL, glass